

# Fluke 77-IV Digital Multimeter

Part No. 01DMFL77-4

*Back to [77-IV Main Page](#)*

- 0.3% basic accuracy
- 3200 count resolution
- Large digital display with analog bargraph
- Backlight for work in dim areas
- Min/Max to record signal fluctuations
- Manual and automatic ranging
- Ergonomic overmolded housing with integrated probe holders
- Sleep mode preserves battery life
- Free your hands with the optional TPAK magnetic hanger
- Meets Measurement Category 1000 V CAT III and Category IV 600 V safety standards



## Specs relating to Fluke 77-IV Digital Multimeter

Voltage DC	Range:	6.000V - 1000V
	Best Accuracy:	+/- (0.3% + 1)
	Best Resolution:	0.1 mV
Voltage AC	Range:	600.0 mV-1000V
	Best Accuracy:	+/- (2.0% + 2)
	Best Resolution:	1.0 mV
Amps AC	Range:	60.00 mA – 10A
	Best Accuracy:	+/- (1.5% + 2)
	Best Resolution:	0.01mA
Amps DC	Range:	60.00 mA – 10A
	Best Accuracy:	+/- (2.5% + 2)
	Best Resolution:	0.01 mA
Resistance	Range:	600.0 $\Omega$ - 50 M $\Omega$
	Best Accuracy:	+/- (0.5% + 1)
	Best Resolution:	0.1 $\Omega$

Capacitance	Range: 1nF- 9,999 $\mu$ F Best Accuracy: +/- (1.2% + 2) Best Resolution: 1 nF
Frequency	Range: 99.99Hz- 99.99kHz Best Accuracy: +/- (0.1% + 1) Best Resolution: 0.01Hz
Safety	ANSI/ISA S82.02.01, CSA C22.2-1010.1, IEC 61010 to 1000 V Measurement Category III, 600 V Measurement Category IV
Certifications	CSA, TÜV (EN61010), UL, П, ; (N10140),VDE

## General Specifications

Maximum voltage between any terminal and earth ground	1000V
Surge protection	8 kV peak per IEC 61010
$\Omega$ Fuse for mA inputs	440 mA, 1000 V FAST Fuse
$\Omega$ Fuse for A inputs	11 A, 1000 V FAST Fuse
Display	Digital: 6000 counts, updates 4/sec Bar Graph: 33 segments; Updates 32/sec Frequency: 10,000 counts Capacitance: 1,000 counts
Altitude	Operating: 2,000 meters Storage: 12,000 meters
Temperature	Operating: -10 °C to +50 °C Storage: -40 °C to +60 °C
Temperature Coefficient	0.1 X (specified accuracy / °C (< 18 °C or > 28 °C))
Electromagnetic Compatibility (EN 61326-1:1997)	In an RF field of 3 V/M, accuracy = specified accuracy except in temperature: specified accuracy $\pm$ 5 °C (9 °F)
Relative Humidity (Maximum Non-condensing)	90 % to 35 °C 75 % to 40 °C 45 % to 50 °C
Battery Life	400 Hours Typical (Alkaline)
Size	Height: 4.3 cm Width: 9 cm Length: 18.5 cm
Weight	420 g