

Back to [e\(E\)PROM Programmer Model LP3](#) Main Page

# Flash Programmer – Two Socket

*Part No. 01LP3*

LEAPER-3C is specially designed for FLASH series, integrating powerful hardware and software to perform high quality . It is the best choice to program FLASH series device. The most attraction of the LEAPER-3C is following 4T products policy, i.e. Light, Thin, Short, Tiny. Con-cerning the concept of environmental protection, the LEAPER-3C avoids unnecessary over-package. LEAP is doing her responsibility for the earth.

## FEATURES

- Small, portable, light & usable with batteries
- Stand-Alone FLASH programmer
- Only one source is needed to copy with.
- Two operation modes:stand-alone&PC mode
- Support Windows 95/98/NT/2000/ME/XP

## STAND-ALONE MODE

- 5 Function keys
  - Functions
  - Type
  - Blank check
  - Verify & check sum
  - Program
- IC parameters are adjustable such as programming algorithm, Vpp voltage, and impulse width.

## PC BASED MODE

- Connect with PC by USB port to transmit data and execute functions such as :  
Type/ Read/ Blank Check/ Program/ Verify/ Erase/ Disk/ Help/ Process/ Parameter
- C parameters are adjustable such as programming algorithm, Vpp voltage, and impulse width.
- File formats supported:  
Binary and machine code, Intel HEX ,  
Motorola HEX

## PHYSICAL & ENVIRONMENTAL SPECIFICATION

- Display: LCD with 16 x 2 characters
- Dimension 16cm x 11cm x 4.5cm
- Weight 0.5Kgs
- Temperature +5°C to +45°C
- Humidity up to 90% non-condensing
- Altitude: up to 5000m

## SAFETY STANDARD

Meet CE requirement

## STANDARD ACCESSORIES

- Main unit
- CD ROM (installation program and user's manual are included)
- USB cable
- 12V/500mA power adaptor

## OPTIONAL ACCESSORIES

- Various PLCC, TSOP, VSOP converters



## SUPPORTED DEVICES

EPROM  
27C64- 27C080  
EEPROM  
28C256-28C040  
FLASH EPROM  
29C256-29C040  
29EE/LE512-29EE/LE020  
28F256-28F020A  
28SF/VF 040  
29F010-29F040  
29F001-29F002  
39SF/VF512-39SF/VF040  
49F512-49BF040  
49F/LV001-49F/LV002