



GFG-8200A Series

GFG-8215A



GFG-8216A



GFG-8217A



GFG-8219A



GFG-8250A



GFG-8255A



FEATURES

- Frequency Range: 0.3Hz ~ 3MHz
- Waveforms: Sine, Triangle, Square, Ramp, TTL and CMOS Output
- External Voltage Controlled Frequency (VCF) Function
- Duty Cycle Control with Signal Inversion Capability
- Variable DC Offset Control
- Two-Step (-20dBx2) and Variable attenuator

- Frequency Range: 0.3Hz ~ 3MHz
- Waveforms: Sine, Triangle, Square, Ramp, TTL and CMOS Output
- External Voltage Controlled Frequency (VCF) Function
- Duty Cycle Control with Signal Inversion Capability
- Variable DC Offset Control
- Two-Step (-20dBx2) and Variable attenuator
- Built-in 6 Digit Counter with INT/EXT Function up to 150MHz

- Frequency Range: 0.3Hz ~ 3MHz
- Waveforms: Sine, Triangle, Square, Ramp, TTL and CMOS Output
- External Voltage Controlled Frequency (VCF) Function
- Duty Cycle Control with Signal Inversion Capability
- Variable DC Offset Control
- Two-Step (-20dBx2) and Variable attenuator
- Built-in 6 Digit Counter with INT/EXT Function up to 150MHz
- LIN/LOG Sweep Mode

- Frequency Range: 0.3Hz ~ 3MHz
- Waveforms: Sine, Triangle, Square, Ramp, TTL and CMOS Output
- External Voltage Controlled Frequency (VCF) Function
- Duty Cycle Control with Signal Inversion Capability
- Variable DC Offset Control
- Two-Step (-20dBx2) and Variable attenuator
- Built-in 6 Digit Counter with INT/EXT Function up to 150MHz
- INT/EXT AM/FM Modulation
- LIN/LOG Sweep Mode
- GCV Output for Synchronization

- Frequency Range: 0.5Hz ~ 5MHz
- Waveforms: Sine, Triangle, Square, Ramp, TTL and CMOS Output
- External Voltage Controlled Frequency (VCF) Function
- Duty Cycle Control with Signal Inversion Capability
- Variable DC Offset Control
- Two-Step (-20dBx2) and Variable attenuator
- Built-in 6 Digit Counter with INT/EXT Function up to 150MHz

- Frequency Range: 0.5Hz ~ 5MHz
- Waveforms: Sine, Triangle, Square, Ramp, TTL and CMOS Output
- External Voltage Controlled Frequency (VCF) Function
- Duty Cycle Control with Signal Inversion Capability
- Variable DC Offset Control
- Two-Step (-20dBx2) and Variable attenuator
- Built-in 6 Digit Counter with INT/EXT Function up to 150MHz
- INT/EXT AM/FM Modulation
- LIN/LOG Sweep Mode
- GCV Output for Synchronization

GW INSTEK

Made to Measure

SPECIFICATIONS

| MODEL | | GFG-8215A/8216A/8217A/8219A | GFG-8250A / 8255A |
|--|---|---|---|
| MAIN | Frequency Range Amplitude Impedance Attenuator DC Offset Duty Control Display Range Accuracy | 0.3Hz ~ 3MHz (7 Range) > 10Vpp (into 50 load) 50 ±10% -20dB ± 1dBx2 <-5V ~ >5V (into 50 load) 80% : 20% : 80% to 1MHz Continue variable 6 digit LED display *GFG-8215A does not have display. ±5%+1Hz (at 3 position) *only for GFG-8215A | 0.5Hz ~ 5MHz (7 Range) > 10Vpp (into 50 load) 50 ±10% -20dB ± 1dBx2 <-5V ~ >5V (into 50 load) 80% : 20% : 80% to 1MHz Continue variable 6 digit LED display |
| SINE WAVE | Distortion Flatness | ≤ 1%, 0.3Hz ~ 200kHz THD ≤ 35dB below fundamental in all range (Specification applied from MAX. to 1/10 level) | ≤ 1%, 0.5Hz ~ 100kHz THD ≤ 30dB below fundamental in all range (Specification applied from MAX. to 1/10 level) |
| TRIANGLE WAVE | Linear | ≥ 98%, 0.3Hz ~ 100kHz ≥ 95%, 100kHz ~ 3MHz | ≥ 98%, 0.5Hz ~ 100kHz ≥ 95%, 100kHz ~ 5MHz |
| SQUARE WAVE | Symmetry Rise or Fall Time | ± 2%, 0.3Hz ~ 100kHz ≤ 100nS at maximum output (into 50 load) | ± 2%, 1Hz ~ 100kHz ≤ 50nS at maximum output (into 50 load) |
| CMOS OUTPUT | Level Rise or Fall Time | 4Vpp ± 1Vpp ~ 14.5Vpp ± 0.5Vpp adjustable ≤ 120nS | 4Vpp ± 1Vpp ~ 14.5Vpp ± 0.5Vpp adjustable ≤ 120nS |
| TTL OUTPUT | Level Fan Out Rise or Fall Time | ≥ 3Vpp 20 TTL load ≤ 25nS | ≥ 3Vpp 20 TTL load ≤ 25nS |
| VCF | Input Voltage Input Impedance | 0V ~ 10V ± 1V (100 : 1) 10k ± 10% | 0V ~ 10V ± 1V (100 : 1) 10k ± 10% |
| GCV (for GFG-8219A/8255A only) | Output Voltage | To set the voltage between 0V ~ 2V as per different frequency | To set the voltage between 0V ~ 2V as per different frequency |
| SWEEP OPERATION (for GFG-8217A/8219A/8255A only) | Sweep/Manual Sweep/Rate Sweep/Time Sweep/Mode | Switch selector 100 : 1 ratio max. and adjustable 0.5sec. ~ 30sec. adjustable Lin./Log. switch selector | Switch selector 100 : 1 ratio max. and adjustable 0.5sec. ~ 30sec. adjustable Lin./Log. switch selector |
| AMPLITUDE MODULATION (for GFG-8219A/8255A only) | Depth MOD. Frequency Carrier BW EXT Sensitivity | 0 ~ 100% 400Hz (INT), DC ~ 1MHz (EXT.) 100Hz ~ 3MHz (-3dB) ≤ 10Vpp for 100% modulation | 0 ~ 100% 400Hz (INT), DC ~ 1MHz (EXT.) 100Hz ~ 5MHz (-3dB) ≤ 10Vpp for 100% modulation |
| FREQUENCY MODULATION (for GFG-8219A/8255A only) | Deviation MOD. Frequency EXT. Sensitivity | 0 ~ ±5% 400Hz (INT), DC ~ 20kHz (EXT.) ≤ 10Vpp for 10% modulation | 0 ~ ±5% 400Hz (INT), DC ~ 20kHz (EXT.) ≤ 10Vpp for 10% modulation |
| FREQUENCY COUNTER (except GFG-8215A) | Int./Ext. Range Accuracy Time Base Resolution Input Impedance Sensitivity | Switch selector 0.3Hz ~ 3MHz (5Hz ~ 150MHz EXT.) Time base accuracy ± 1 count ± 10ppm (23 °C ± 5 °C) after 30 minutes warm up The maximum resolution is 100nHz for 1Hz and 1Hz for 100MHz 1M // 150pF ≤ 35mVrms (5Hz ~ 100MHz) ≤ 45mVrms (100MHz ~ 150MHz) | Switch selector 0.5Hz ~ 5MHz (5Hz ~ 150MHz EXT.) Time base accuracy ± 1 count ± 10ppm (23 °C ± 5 °C) after 30 minutes warm up The maximum resolution is 100nHz for 1Hz and 1Hz for 100MHz 1M // 150pF ≤ 35mVrms (5Hz ~ 100MHz) ≤ 45mVrms (100MHz ~ 150MHz) |
| GENERAL INFORMATION | Power Source Accessories Dimension Weight | AC115V, 230V ± 15%, 50 / 60Hz GTL-101 x 2 (GTL-101 x 1 for GFG-8215A) User manual x 1 251 (W) x 91 (H) x 291 (D) Approx. 2.0 kgs (GFG-8215A) Approx. 2.15kgs (GFG-8217A) Approx. 2.1 kgs (GFG-8216A) Approx. 2.2 kgs (GFG-8219A) | AC115V, 230V ± 15%, 50 / 60Hz GTL-101 x 2 User manual x 1 251 (W) x 91 (H) x 291 (D) Approx. 2.3 kgs (GFG-8250A) Approx. 2.4 kgs (GFG-8255A) |

Specifications subject to change without notice. FG-820AGD0DH